



The Measure of Quality


MIC-4070D HAND-HELD LCR METER

- 0.1 μ H to 200H Inductance Measurement
- 0.1pF to 20000 μ F Capacitance Measurement
- 1m Ω to 20M Ω Resistance Measurement
- Dissipation Factor Measurement
- Zero Adjustment
- Quick Responding of Measurement



TL-06 SMD TESTING PROBE

The optional accessory for MIC-4070D and MIC-4060D, which is special designed for measuring the SMD (Surface Mount Device) type Resistor, Capacitor and inductor.



• MIC-4070D



• MIC-4060D
(Discontinued)

MIC-4070D DIGITAL LCR METER

Measurement Range And Accuracy

CAPACITANCE

Range	Accuracy	Resolution	Test Condition
200pf	1%+2	0.1pf	Parallel Mode 1KHz, 0.5Vrms
2nf		1pf	
20nf		10pf	
200nf		100pf	
2μf		1000pf	
20μf	2%+10	0.01μf	Series Mode 120Hz, 1mA rms
200μf		0.1μf	
2mf		1μf	
20mf		10μf	
200mf		100μf	


DISSIPATION FACTOR

Range	Accuracy			
0 ~ 1.999	200pf	2nf ≤ Cx ≤ 2μf	2μf < Cx ≤ 2mf	20mf
	N.S.	1% + 10 + $\frac{2000}{Cx}$	2% + 20 + $\frac{2000}{Cx}$	N.S.


Cx is capacitance readout in counts.

Accuracy is applied when C is from 20 to 100% of full scale range in series mode measurements.

Parallel Mode $D_c = \frac{1}{2\pi f C_p R_p}$



Series Mode $D_c = 2\pi f C_s R_s$



INDUCTANCE

Range	Accuracy	Resolution	Test Condition
200μH	2%+2	0.1μH	Series Mode 10mA rms, 1KHz
2mH		1μH	
20mH		10μH	
200mH	1%+2	100μH	
2H		1mH	Parallel Mode 120Hz, 0.5Vrms
20H		10mH	
200H	3%+2	100mH	

The accuracy is applied from 10 to 100% of full scale range in parallel mode measurements.


DISSIPATION FACTOR

Range	Accuracy	
0 ~ 1.999	$L_x \leq 200mH$	$200mH < L_x < 200H$
	$1\% + 10 + \frac{2000}{L_x}$	$2\% + 20 + \frac{2000}{L_x}$


Lx is inductance readout in counts.

Accuracy is applied when L is from 20 to 100% of full scale range in parallel mode measurements.

Parallel Mode $D_L = 2\pi f \frac{L_p}{R_p}$



Series Mode $D_L = \frac{R_s}{2\pi f L_s}$



RESISTANCE

Range	Accuracy	Resolution	Test Condition
2Ω	1%+5	1mΩ	Series Mode 1KHz
20Ω		10mΩ	
200Ω		100mΩ	
2KΩ		1Ω	
20KΩ		10Ω	
200KΩ		100Ω	
2MΩ	2%+2	1KΩ	Parallel Mode 1KHz, 0.5Vrms
20MΩ		10KΩ	

Accuracy is ± (% of reading + number of digits) and is applied from 10 to 100% of full scale range in parallel mode measurements.

The specifications given assume an operating temperature of 18°C to 28°C humidity up to 80%, and half year calibration cycle.

GENERAL SPECIFICATIONS

Power	Single 9V 006P battery	
Display	0.5" digital height, 3 1/2 digits liquid crystal display with "LOBAT" and decimal annunciators	
Low Battery Warning	Display will show "LOBAT" in the last 5% of battery life	
Current Consumption	17.3mA	
Temperature	0°C ~ 40°C, Operating -20°C ~ 70°C, Storage	
Dimensions	177x88x40mm	
Weight	400 grams	
Standard Accessories	Test Clips (red & black)	1 pair
	Operation Manual	1 piece
Optional Accessories	Measurement clip TL-06 for SMD type component	

MOTTECH

MOTTECH INDUSTRIES INC.

茂迪股份有限公司

6F., No. 248, Pei-Shen Rd., Sec. 3, Shen Keng Hsiang,

Taipei Hsien, Taiwan

Tel: 886-2-2662-5093 Fax: 886-2-2662-5097

URL: www.motechind.com E-mail: t&m@motechind.com