



VP-440

Non-Contact VoltProbes®

Designed for safety and limited troubleshooting without the expense. Fits conveniently in a shirt pocket, tool belt, or pouch.

VP-440RT Non-Contact VoltProbe

- Locating of circuit breakers
- Voltage range: 110 - 600 V AC
- Locating of defective fuses
- No disconnection of electrical system necessary
- Uses non-contact method of Voltage testing
- Test for AC Voltage cables, wall sockets, junction boxes, etc.
- Safety acc. EN 61010, CAT III/600 V



VP-600SB Non-Contact VoltProbe

- Detect AC Voltage (100 - 600 V)
- Use non-contact method of Voltage testing
- Totally insulated, no exposed metal or conductive parts
- Check for AC Voltages without necessity of disconnecting the electrical system
- Test for AC Voltage cables, circuit breakers, wall sockets, junction boxes, fuses, etc.
- Safety acc. EN 61010, CAT III/600 V



| FEATURES | VP-440 | VP-600SB |
|----------------------|-------------|----------------------------|
| AC Voltage Detection | 100 - 600 V | |
| Indicator | Lights | Lights, Beeps and Vibrates |

VT201A Non-Contact Voltage Detector

- Quickly check for the presence of AC voltages, with no electrical contact
- Safe non-contact detection of voltages from 70 V to 440 V AC
- Both visible and audible indicators
- Detector emits loud audible chirping
- Bright flashing LED
- On/Off button beep confirms unit and batter is working



MT-1000L Non-Contact Magnetic Tester

- Non-contact magnetic field tester with torch function
- Build-in magnetic field sensor enables magnetic fields to be detected
- The test tip lights up immediately without any metal contact as soon as a magnetic field is detected
- The test lamp reacts to all magnetic fields in three-phase current, direct current and permanent magnets
- Testing of Solenoid Valves
- Ultrabright LED
- incl. Test Magnet and Batteries



Voltage & Continuity Testers

Multitest Sigma Voltage and continuity tester with phase rotation

- 12 V to 690 V AC & DC voltage range
- Continuity test (optical + sound)
- Phase rotation test
- Polarity indication
- Phase testing
- Data Hold function
- 30 mA RCD trip test
- Undetachably tip protection
- IP65 water jet and dust tight protection
- Safety acc. EN 61010, CAT III/600 V

