



APPA 31

AC 400A capability  
 1.9% basic accuracy  
 Non-intrusive transducing  
 Up to 29mm diameter conductor  
 5 feet drop proof  
 Coiled cable output plugs  
 Ergonomically designed jaw and trigger  
 Hand guard designed  
 Carrying case included  
 IEC 1010-1 CAT II 600V



APPA 32

AC/DC 600A capability  
 Dual Hall sensor  
 2.0% basic DCA/ACA accuracy  
 Non-intrusive transducing  
 Up to 34mm dia conductor  
 Up to 20x40mm busbar  
 DCA zero adjust knob  
 Power on indicating  
 Battery low indicator  
 5 feet drop proof  
 Coiled cable output plugs  
 Hand Guard protection  
 Carrying case included  
 IEC 1010-1 CAT II 600V



APPA 30T

AC/DC 300A capability  
 Auto zero key for DCA  
 Red LED-Low battery indication  
 GreenLED-Power on indication  
 Coiled cable output leads  
 Insulated input jacks  
 Standard 9V battery  
 Up to 22mm dia. conductor  
 4 feet drop proof  
 Deluxe carrying case  
 Hand guard designed  
 IEC 1010-1 CAT. III 600V Safety Standard



APPA 39T

AC/DC 1000A capability  
 Auto zero key for DCA  
 Red LED-Low battery indication  
 GreenLED-Power on indication  
 Coiled cable output leads  
 Insulated input jacks  
 Standard 9V battery  
 Up to 51mm dia. (2") conductor  
 Up to 24x60mm busbar  
 4 feet drop proof  
 Deluxe carrying case  
 Hand guard designed  
 IEC 1010-1 CAT. III 1000V Safety Standard



**APPA 35N**  
**APPA 35R (True-RMS reading)**

4000 count digital display  
AC 400A, 600V Capability  
Autoranging  
1.2% basic ACV accuracy  
1.9% basic ACA accuracy  
1.9% basic OHM accuracy  
Continuity buzzer  
Up to 29mm (600MCM) conductor  
600V circuit protection  
Display hold function  
Auto power off  
4 feet drop proof  
Insulated input jacks  
Hand guard protection  
Deluxe carrying case  
IEC 1010-1 CAT II 600V



**APPA 33RII**  
**APPA 33RII (True-RMS reading)**

2000 count large scale LCD display  
AC 600 Amps capability  
AC 600 Volts capability  
2000 Ohms Resistance range  
True RMS ACV/ACA (APPA33RII)  
Continuity Beeper  
Display Hold  
Auto power off  
600 Volts circuit protection  
Insulated input jacks  
Up to 34mm dia. (750MCM) conductor  
4 feet drop proof  
Protective carrying case  
Hand guard designed  
CAT. III 600V/CAT. II 1000V Safety Standard



**APPA 39AC**  
**APPA 39AR (True-RMS reading)**

4000 count digital display  
AC 1200A in specification  
AC 1000A in specification (39AR)  
1500A overload protection  
AC 600A, DC 1000V capability  
Autoranging  
1.2% basic ACV accuracy  
1.2% basic DCV accuracy  
2% basic OHM accuracy  
CONTINUITY beeper  
**True RMS reading in ACV/ACA**  
Up to 51mm dia. (2") conductor  
600V circuit protection  
Display HOLD function  
Auto Power Off  
Insulated input jacks  
Hand guard designed  
Deluxe carrying case  
IEC 1010-1 CAT. II 1000V



**APPA 33**  
**APPA 33R (True-RMS reading)**

4000 count digital display  
AC 600A, 600V Capability  
Autoranging  
1.2% basic ACV accuracy  
1.9% basic ACA accuracy  
1.9% basic OHM accuracy  
Continuity beeper  
Up to 40mm dia. (750MCM) conductor  
600 Volts circuit protection  
Display hold function  
Auto power off  
4 feet drop proof  
Insulated input jacks  
Hand guard designed  
Deluxe carrying case  
IEC 1010-1 CAT II 600V

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-54151736  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

# AC/DC CURRENT CLAMP MULTIMETER

## APPA 30

### APPA 30R (True-RMS reading)

4000 count digital display  
 Autoranging  
 Dual Hall sensor  
**Nickel-Steel alloy jaw mechanism**  
 AC/DC 300 Amps capability  
 AC/DC 600 Volts capability  
 0.5% basic DCV accuracy  
 1.5% basic ACV accuracy  
**1.0% basic DCA/ACA accuracy**  
 0.9% basic OHM accuracy  
 Continuity Beeper  
 10mA resolution  
 Auto-Zeroing key for DCA  
 Data hold function  
 MAX hold function  
 Auto power off selectable  
 600V protection in every range  
 Up to 22mm dia (350 MCM) conductor  
 4 feet drop proof  
 Insulated input jacks  
 Hand guard designed  
 Deluxe carrying case  
 IEC 1010-1 CAT II 600V



## APPA 36II

### APPA 36R11 (True-RMS reading)

4000 count large scale LCD display  
 Autoranging  
 Dual Hall Sensor  
 AC/DC 600 Amps capability  
 AC/DC 600 Volts capability  
 40M Ohms Resistance range  
**True RMS ACV/ACA (APPA36R11)**  
 Continuity Beeper  
 Display Hold  
 Maximum Hold  
 Auto-Zeroing Key for DCA  
 Auto power off selectable  
 600Volts Circuit protection  
 Insulated input jacks  
 Up to 35mm dia. (750MCM) conductor  
 Up to 40x15mm busbar  
 4 feet drop proof  
 Deluxe carrying case  
 Hand guard designed  
 CAT.III 600V Safety Standard



### APPA 39MR (True-RMS reading)

4000 count digital display  
**AC/DC 1000A in specification,  
 and 2000A overload protection**  
**AC 600V, DC 1000V capability**  
 Autoranging

Dual Hall sensor  
**Nickel-Steel alloy jaw mechanism**  
 0.7% basic DCV accuracy  
 1.2% basic ACV accuracy  
**1.0% basic DCA/ACA accuracy**  
 1.5% basic ACA accuracy  
 1.0% basic OHM accuracy  
 0.5% basic Hz accuracy  
 CONTINUITY beeper  
**True RMS reading in ACV/ACA**  
 Frequency measurement through  
 input jack or clamp-on  
 PEAK HOLD function  
**Auto-Zero key for DCA**  
**Auto Power Off**  
 Up to 51mm dia. (2") conductor  
 Up to 24 x 60mm busbar  
 4 feet drop proof  
 Insulated input jacks  
 Hand guard designed  
 Deluxe carrying case  
 IEC 1010-1 CAT.II 1000V



## APPA 39

### APPA 39R (True-RMS reading)

4000 count digital display  
 AC/DC 1000A in specification,  
 and 2000A overload protection  
 Autoranging  
 Dual Hall sensor  
 1.9% basic DCA/ACA accuracy  
 0.5% basic Hz accuracy  
 Frequency measurement by  
 clamp-on  
 Peak hold function  
 Auto zero key for DCA  
 Auto power off  
 Up to 51mm dia. (2") conductor  
 Up to 24x60mm busbar  
 4 feet drop proof  
 Hand guard designed  
 Deluxe carrying case  
 IEC 1010-1 CAT. II 1000V

