

Analogue insulation testers

- > Always ready thanks to their magneto power supply
- > Robust housing for work in all conditions

IMEG 500N

Insulation 500 V, continuity and resistance



IMEG 1000N

Insulation 1000 V



C.A 6511

- > Simple, economic and shockproof
- Analogue
- Insulation 500 V, continuity and resistance

C.A 6513

- > Simple, economic and shockproof
- Analogue
- Insulation 1000 V, continuity and resistance



	IMEG 500N	IMEG 1000N	C.A 6511	C.A 6513
Reference	> P01.1325.01A	> P01.1325.02A	> P01.1402.01	> P01.1403.01
Voltage	0 to 600 VAC	0 to 600 VAC	0 to 600 VAC	0 to 600 VAC
Insulation	500 VDC	250 / 500 / 1000 VDC	500 V	500 / 1000 VDC
Range	0.5 to 200 MΩ	1 to 5000 MΩ	0.1 to 1000 MΩ	0.1 to 1000 MΩ
Continuity	0 to 100 Ω		-10 Ω to +10 Ω	-10 Ω to +10 Ω
Current reversal			yes	yes
Resistance	0 to 500 kΩ			0 to 1000 Ω
Display	analogue	analogue	analogue	analogue
Power supply	magneto	magneto	4 x 1.5 V batteries	4 x 1.5 V batteries
Electrical safety	600 V as per IEC 414	600 V as per IEC 414	IEC 61010 Cat. III 600 V	IEC 61010 Cat. III 600 V
Dimensions	120 x 120 x 130 mm	120 x 120 x 130 mm	167 x 106 x 55 mm	167 x 106 x 55 mm
Weight	1500 g	1500 g	500 g	500 g
State of delivery			2 leads, 1 crocodile clip, 1 test probe	2 leads, 1 crocodile clip, 1 test probe
Dedicated accessories	Pouch containing IPA 2 test accessories			