



**Specifications**

Model	Range	9801A+	9804A+	9806+	9807A+	9808+	980+
DC V	200mV/2V/20V/200V/1000V	±(0.5%+3)	±(0.5%+3)	±(0.05%+5)	±(0.1%+5)	±(0.5%+3)	±(0.05%+5)
	2V/20V/200V/1000V	±(0.8%+5)	±(0.8%+5)	---	---	---	---
AC V	200mV/2V/20V/200V/750V	---	---	±(0.8%+25)	±(0.8%+2)	±(0.8%+5)	±(0.8%+25)
	200uA/2mA/20mA/200mA/2A/20A	±(1.2%+8)	---	---	---	---	---
DC A	200uA/2mA/20mA/200mA/20A	--	±(1.2%+8)	---	---	±(1.2%+8)	---
	200uA/2000uA/20mA/200mA/20A	---	---	±(0.5%+4)	±(0.5%+4)	---	---
	200uA/2000uA/20mA/200mA/2A/20A	---	---	---	---	---	±(0.5%+4)
AC A	200mA/2A/20A	±(1.5%+15)	---	---	---	---	---
	200mA/20A	---	±(1.5%+15)	---	---	---	±(1.5%+15)
	20mA/200mA/20A	---	---	±(1.5%+15)	±(1.5%+15)	---	---
	200uA/2mA/20mA/200mA/20A	---	---	---	---	±(1.5%+15)	---
Resistance	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ/200MΩ	±(0.8%+3)	±(0.8%+3)	±(0.4%+5)	±(0.4%+5)	±(0.8%+3)	±(0.4%+5)
	Capacitance	6nF/60nF/600nF/6uF/60uF/600uF/6mF/20mF	±(3.5%+20)	±(3.5%+20)	---	---	---
20nF/200nF/2uF/20uF/200uF/2mF		---	---	±(4.0%+50)	±(4.0%+50)	±(3.5%+20)	±(4.0%+50)
Frequency	10Hz/100Hz/1KHz/10KHz/100KHz/1MHz/20MHz	---	±(1.0%+10)	---	---	±(1.0%+10)	---
	200Hz/2KHz/20KHz/200KHz/2MHz	---	---	±(0.1%+3)	±(0.1%+3)	---	±(0.1%+3)
Temperature	-20 ~ 1000°C/(-4 - 1832) °F	---	±(1.0%+5)	---	---	±(1.0%+5)	---
Inductance	2mH/20mH/200mH/2H/20H	---	---	---	---	±(2.5%+30)	---
Conductivity	0.1-100ns	---	---	±(1.0%+30)	±(1.0%+30)	---	---

**General Information**

Model	9801A+	9804A+	9806+	9807A+	9808+	980+
Power supply	1.5V, AAA*2					
Product color	Black+ orange					
Product weight	395g					
Product size	186×92×52 mm					
Standard accessories	Test leads, batteries, manual, temperature probe (for 9804A+,9808+)					

