



MD 106
Metrel



MD 116
Metrel



AC 15
CEM



VF 3
Megger



VP 52
FLIR



testo 745
Testo



NCV 1030
Amprobe



NCV 1040
Amprobe



Fluke 1AC II
Fluke

	MD 106 Metrel	MD 116 Metrel	AC 15 CEM	VF 3 Megger	VP 52 FLIR	testo 745 Testo	NCV 1030 Amprobe	NCV 1040 Amprobe	Fluke 1AC II Fluke
Rozsah (AC)	90 - 1000 V	12 - 90 V 90 - 1000 V	12 - 1000 V 100 - 1000 V	90 - 600 V	24 - 1000 V 190 - 1000 V	12 - 50 V 50 - 1000 V	12 - 50 V 50 - 1000 V	12 - 50 V 50 - 1000 V	200 - 1000 V
Frekvencia	50 - 60 Hz	40 - 400 Hz		50 - 60 Hz	45 - 65 Hz	40 - 400 Hz	50 - 400 Hz	50 - 400 Hz	
Signalizácia	optická akustická vibrácia	optická akustická	optická akustická	optická akustická	optická vibrácia	optická akustická	optická akustická	optická akustická	optická akustická
Iné			APO, pád 2m		pád 3m	VF filter	APO	APO, mag.pole	
LED svetlo	Áno		Áno	Áno	Áno		Áno	Áno	
Kategória	CAT IV 1000V	CAT IV 1000V	CAT IV 1000V	CAT IV 600V	CAT IV 1000V	CAT IV 1000V	CAT IV 1000V	CAT IV 1000V	CAT IV 1000V
Krytie	IP 65	IP 65	IP 67	IP 65		IP 67	IP 65	IP 65	
Teplota okolia	-10 ... +50°C	0 ... +40°C		-10 ... +50°C		-10 ... +50°C	0 ... +40°C	0 ... +40°C	
Rozmery	155 x 25 mm	155 x 25 mm	160 x 25 mm	178 x 26 mm		155 x 25 mm	156 x 27 mm	156 x 27 mm	
Hmotnosť	56 g	58 g	55 g	48 g		63 g	60 g	62 g	
Napájanie	2 x 1,5V AAA	2 x 1,5V AAA	2 x 1,5V AAA	2 x 1,5V AAA	2 x 1,5V AAA	2 x 1,5V AAA	2 x 1,5V AAA	2 x 1,5V AAA	2 x 1,5V AAA

APO ... automatické vypnutie