



V DC 600V
AC 600V

A DC 10A
AC 10A

Specifications	Range	Resolution	MY70	MY74	MY74B	
			Accuracy			
DC Voltage	200mV/2V/20V/200V	0.1mV/1mV/10mV/0.1V	±(0.5%+2)	±(0.5%+2)		
	600V	1V	±(0.8%+2)	±(0.8%+2)		
AC Voltage	200mV	0.1mV	±(1.2%+3)			
	2V/20V/200V	1mV/10mV/0.1V	±(0.8%+3)	±(0.8%+3)		
	600V	1V	±(1.2%+3)	±(1.2%+3)		
DC Current	20µA	0.01µA	±(2.0%+5)	±(2.0%+5)		
	200µA	0.1µA	±(0.8%+1)			
	2mA	1µA	±(0.8%+1)	±(0.8%+1)		
	20mA	10µA	±(0.8%+1)	±(0.8%+1)		
	200mA	0.1mA	±(1.5%+1)	±(1.5%+1)		
AC Current	10A	0.01A	±(2.0%+5)	±(2.0%+5)		
	20µA	0.01µA	±(2.0%+5)			
	200µA	0.1µA	±(1.0%+5)			
	2mA	1µA	±(1.0%+5)			
	20mA	10µA	±(1.0%+5)	±(1.0%+5)		
Resistance	200mA	0.1mA	±(1.8%+5)	±(1.8%+5)		
	10A	0.01A	±(3.0%+7)	±(3.0%+7)		
	200Ω	0.1Ω	±(0.8%+3)	±(0.8%+3)		
	2kΩ/20kΩ/200kΩ/2MΩ	1Ω/10Ω/0.1kΩ/1kΩ	±(0.8%+2)	±(0.8%+2)		
Capacitance	20MΩ	10kΩ	±(1.0%+2)	±(1.0%+2)		
	200MΩ	0.1MΩ	±(6.0%+10)	±(6.0%+10)		
	2nF/20nF/200nF/2µF	1pF/10pF/0.1nF/1nF		±(4.0%+3)		
Frequency	100µF	0.1µF		±(6.0%+10)		
	20kHz	0.01kHz		±(2.0%+5)		
Temperature	-20°C~0°C	1°C		±(5.0%+4)		
	1°C~400°C	1°C		±(2.0%+3)		
	401°C~1000°C	1°C		±(2.0%+5)		
Features						
Display	counts			2000		
APO	Auto Power Off			•		
Transistor hFE	0~1000			•		
Diode	Open Voltage			3.0V		
Continuity Buzzer	<50Ω			•		
Data Hold				•		
LBD	Low Battery Display			•		
General						
Power Supply	1×9V 6F22 Battery					
Product Size	188mm×93mm×50mm/7.4"×3.7"×1.96"					
Product Weight	380g/0.84lb					
Certificate	CE/ETL/RoHS					
Safety Rating	CAT III 600V					

Accessories Included

- Test Leads
- K type thermocouple (MY74 / MY74B)
- Multi-Function Socket
- Battery and User's manual

